

## InLine Tag™ Ultra



### ROBUST, ALL-PURPOSE UHF RFID TAGS MOUNT TO ANY SURFACE MATERIAL AND DELIVER LONG READ RANGES

- **Extreme durability** – resistant to outdoor elements as well as blunt and sharp impact
- **Multiple mounting options** – glue, screw or weld
- **Enhanced reliability** – read-write on any material, up to 26 ft (8 m)
- **Broadband frequency** – for worldwide use, including Europe, the United States and Japan

HID Global's InLine Tag™ Ultra passive contactless transponders are the most advanced general-purpose UHF tags available in the market. Choose from options that mount on any material while enabling read ranges of up to a 26 ft (8 m), with no line-of-sight.

InLine Tag devices improve data collection speed and accuracy for logistics applications, while making tracking more cost-effective. These tags enable complete accuracy of asset identification. For example, it is possible to track hundreds of metal kegs containing liquid loaded on a truck as it moves slowly through RFID reader enabled gates placed at points of distribution and delivery.

UHF technology enables anti-collision functionality, fast data-rate communication and password data protection for precise, reliable reading and updating of each tag's 512-bit read-write memory. All InLine Tag RFID tags are compliant with EPC global-certified UHF Class 1 Gen 2 readers and modules, with broadband capability for international operations.

The tough and versatile InLine Tag transponders are available for mounting on metal, plastic or wood using standard M5 screws, industrial adhesives or welding. The tags are lightweight, waterproof and resist high-pressure/high temperature washing conditions according to the highest standard (IP69K).

InLine Tag Ultra RFID tags include HID Global's patented 3D antenna, enabling omnidirectional read range performance independent of mounting material. The tags also enable maintenance of separate public and private profiles for added data security.

The InLine Tag Ultra Curve version is arched to hug metallic kegs or gas cylinders, and durably withstands typical washing and disinfection cycles. Slim versions of the tags enable UHF performance for space-restricted applications, and are configured for attachment via screw or weld.

#### TECHNOLOGY HIGHLIGHTS:

- Worldwide operating frequencies from 860 to 960 MHz
- Fully interoperable; standards compliant
- Reliable performance on both metal and non-metal surfaces
- Waterproof under high pressure / high temperature conditions; chemical and impact resistant
- Mounting options include nails, screws, welding and glues
- Large memory of up to 512-bit user memory and 128-bit EPC number

### APPLICATION AREAS:

- **Asset tracking and logistics**
  - Postal and road toll management: truck, wagon and train tracking
  - Supply chain management: pallet and goods tracking
- **Returnable transport items**
  - Shipping container tracking
  - Metal keg and gas cylinder identification
- **Waste management**
  - Commercial and industrial bin identification

## SPECIFICATIONS



HID Global can create a custom tag solution to fit your application requirements for chip type, dimensions, programming and materials.

North America: +1 949 732 2000  
 Toll Free: 1 800 237 7769  
 Europe, Middle East, Africa: +41 21 908 01 00  
 Asia Pacific: +852 3160 9800  
 Latin America: +52 (55) 5081 1650

[hidglobal.com](http://hidglobal.com)

**ASSA ABLOY**

An ASSA ABLOY Group brand

© 2013 HID Global Corporation/ASSA ABLOY AB. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design and InLine Tag are trademarks or registered trademarks of HID Global or its licensor(s)/supplier(s) in the US and other countries and may not be used without permission. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.  
 2013-11-27-hid-rfid-il-inline-tag-ultra-family-ds-en

InLine Tag™ Ultra					
		Weld	Slim	Slim Weld	Curve
<b>Base Model Number</b>	6A7980 (blue) 6A7980-102 (grey)	6A7981	6A7983	6A7984	6A7982
<b>ELECTRONIC</b>					
<b>Operating Frequency</b>	865-956 MHz (EU, US, JP)				
<b>Chip Type</b>	Monza 4QT				
<b>Memory</b>	128 bit EPC + 96 bit TID + 512 bit user memory				
<b>Anti-Collision</b>	Yes				
<b>Reading Distance</b> (2W reader ERP, free space)	Up to 26.2 ft (8 m)	Up to 16.4 ft (5 m)		Up to 26.2 ft (8 m)	
<b>PHYSICAL</b>					
<b>Dimensions</b>	3.8 x 1.1 x 0.6 in (97 x 27 x 15 mm)	4.1 x 1.4 x 0.6 in (105 x 35 x 15 mm)	3.8 x 1.1 x 0.4 in (97 x 27 x 10 mm)	4.1 x 1.4 x 0.4 in (105 x 35 x 10 mm)	3.5 x 1.5 x 0.6 in (88 x 37 x 14.5 mm); 1.7 in (45 mm) curve radius
<b>Mounting Method</b>	Screw	Weld	Screw	Weld	
<b>Screw Mounting Hole</b>	Ø 0.2 in (5.2 mm)		Ø 0.2 in (5.2 mm)		
<b>Affixes To</b>	All surfaces, including metal, plastic, wood				Curved metal
<b>Housing Material</b>	PC/ABS high impact	PC/ABS high impact, stainless steel ring	PC/ABS high impact	PC/ABS high impact, stainless steel ring	
<b>Color</b>	Pantone blue 287C or grey (custom colors available)				
<b>Weight</b>	0.5 oz (16 g)	0.6 oz (18 g)	0.4 oz (12 g)	0.5 oz (14 g)	0.5 oz (15 g)
<b>CHEMICAL AND MECHANICAL</b>					
<b>Water</b>	IP69K, 176° F (80° C), 100 bar, 30 sek. 16 l/min				
<b>Withstands Exposure To</b>	Mineral oil, petroleum, salt mist, vegetable oil; up to 80% humidity at 158° F (70° C)				
<b>Environmental Test Conditions</b>	68° F (20° C), 100 h				
<b>Vibration</b>	IEC 68.2.6 [10 g, 10 to 2000 Hz, 3 axis, 2.5 h]				
<b>Shock</b>	IEC 68.2.29 [40 g, 18 ms, 6 axis, 2000 times]				
<b>Impact</b>	IEC 62262-IK09				IEC 62262-IK08
<b>Axial/Radial Force</b>	1000 N, 10 sec				
<b>THERMAL</b>					
<b>Storage</b>	-40° to +176° F (-40° to +80° C), 1x1000 h				
<b>Operating Temperature</b>	-40° to +176° F (-40° to +80° C)				
<b>Shock/Fatigue</b>	-40° to +185° F (-40° to +85° C), 100 x 5 min with 20 sec transition				
<b>OTHER</b>					
<b>Standards</b>	UHF EPC Class 1 Gen 2, ISO 18000-6C, ISO 17364, DIN 40050-9				
<b>Options</b>	Custom embossed logo, no logo or custom tag color. Laser engraving of custom logo, barcode or text on grey tag versions. By default, grey tags are supplied without logo or laser engraving.				
<b>Box Size</b>	240 pcs.	360 pcs.		240 pcs.	
<b>Warranty</b>	2 Years				